



PRODUCT DATA: ANTI-MOISTURE COATING

Waterproofing paint to seal water stains or wet areas by infiltration, capillary, etc.. Breathable

TECHNICAL CHARACTERISTICS

Nature:	Synthetic.
Finish:	Matte.
Colour:	White
Density:	1,6 Kg/Litre
Spread Rate	high
Drying time	Dry to touch 2 hours. Over-coating time: 24 hours
Packaging	14 litres, 4 Litres, 750 ml.

We assume no liability if the result is affected by factors beyond our control. The user should check that the product supplied fits the needs for which it is intended and must perform a preliminary test if necessary. The information contained in this form should be used like a guide but not like a warranty. For more information in relation to safety and environment, see data safety sheet of the product



PRODUCT DATA: ANTI-MOISTURE COATING

APPLICATION

On concrete, cement, stone, etc. even if wet, in basements, garages, cellars, bathrooms, etc.

INSTRUCTIONS:

Application: Brush, Roller.

Thinner and tools cleaning : Synthetic solvent 103-X.

Unpainted surfaces: Remove existing dust and salt with a stiff brush .

The surfaces in poor condition should be repaired before painting.

Painted surfaces: Remove the old paint and efflorescence, until reaching the healthy support.

Then proceed as in new areas.

Anti-Moisture Coating can be used as a finish, but it is advisable to apply another topcoat (plastic or synthetic).

CAUTIONS:

Flammable.

Stir the contents of the pack.

Use under adequate ventilation. Avoid prolonged inhalation and use mask if necessary.

