



PRODUCT DATA: ANTI-SMOKE SEALER

Plioway resin-based insulating paint, monolayer, odorless and resistant to alkalis

TECHNICAL CHARACTERISTICS

Nature:	Synthetic.
Finish:	Matte.
Colour:	White
Density:	1,5 Kg/Litre
Spread Rate	5-6 m2/Litre coat
Drying time	Dry to touch 2 hours. Over-coating time: 6 hours
Packaging	4 Litres, 750 ml.

We assume no liability if the result is affected by factors beyond our control. The user should check that the product supplied fits the needs for which it is intended and must perform a preliminary test if necessary. The information contained in this form should be used like a guide but not like a warranty. For more information in relation to safety and environment, see data safety sheet of the product



PRODUCT DATA: ANTI-SMOKE SEALER

APPLICATION

Suitable for kitchen ceilings, bathrooms, etc. due to its insulating power of dark spots smoke, grease, fumes, etc...

INSTRUCTIONS:

Application: Brush, Roller.

Thinner and tools cleaning : solvent.

Ready to use, does not need dilution.

New dry surfaces: apply directly.

Surfaces in poor condition: remove old paints badly adhered



CAUTIONS:

Flammable.

Stir the contents of the pack.

Use under adequate ventilation. Avoid prolonged inhalation and use mask if necessary.

