



PRODUCT DATA: MULTICOLOUR FLASH VARNISH

Transparent plastic varnish .Once dry, produces multicoloured flashes thanks to its high content of coloured satin particles. It is indicated as a topcoat on plastic paints. In addition to providing a decorative finish, it improves the resistance and washability of the surface on which it is applied.

PROPERTIES AND TECHNICAL CHARACTERISTICS:

- Easy to apply.
- Quick drying.
- Good adhesion
- Multicolour Finish
- High wet abrasion resistance
- Viscosity: 135 UK
- Density: 1.06 kg / l.
- Drying time: 1 -3 hours depending on the surface.

We assume no liability if the result is affected by factors beyond our control. The user should check that the product supplied fits the needs for which it is intended and must perform a preliminary test if necessary. The information contained in this form should be used like a guide but not like a warranty. For more information in relation to safety and environment, see data safety sheet of the product



PRODUCT DATA: MULTICOLOUR FLASH VARNISH

APPLICATIONS

Interior walls

INSTRUCTIONS:

Dilution: Dilute in 8-10% water. Can be applied with a brush, roller or paint sprayer. Surfaces to be painted must be free of impurities such as dust, efflorescence, rust, grease, waxes and moisture

PACKAGING:

1 or 5 litres.

CAUTIONS:

Do not apply under 5°C or over 40°C in the sun. Keep containers out of direct radiation. Keep out of reach of children

