



## PRODUCT DATA: SYNTHETIC VARNISH

### 1. DESCRIPTION

Glossy varnish for wood.

Hard and elastic, excellent wear resistance. Excellent glossy and transparent varnish

### 2. APPLICATIONS

Decoration and protection of natural or stained wood, such as doors, cabinets, windows, etc.

### 3. TECHNICAL CHARACTERISTICS:

Nature:	Alkyd .
Finish:	Gloss, Satin or Matte.
Colour:	Colourless
Density:	0,90 Kg/L.
Spread rate:	14-18 m <sup>2</sup> /Litre / coat
Drying time:	Dry to touch : 1-2 hours, Over-coating 12-14 hours
Packaging	0,75, 4 and 20 Litres



## PRODUCT DATA: PRODUCT DATA: SYNTHETIC VARNISH

### 4. INSTRUCTIONS:

Apply on sanded, clean and dry surfaces.

**New wood:** Exterior: Apply 2 or 3 coats on a previously applied Protective Primer

Interior: apply directly 2 or 3 coats.

**Varnished wood:** If the varnish is in good condition, sand and varnish directly. If it is in poor condition, remove completely and proceed as in new wood

**Old unpainted wood:** Remove completely the grayish and parched surface by sanding or slashing thoroughly until reaching the wood in good condition

### 5. CAUTIONS.

Flammable.

Use under adequate ventilation. Avoid prolonged inhalation and use mask if necessary.

Stir the contents of the pack.

