



## PRODUCT DATA : BASE PAINT

Matte paint available in different colours depending on the colours chart. Could be applied directly on the surface or be used to obtain different colour schemes.

Product	Plastic base paint
Application	Interior and exterior use ( depending on the colour)
Tools	Brush , Roller or Paint Sprayer.
Colour	See colours chart
Finish	Matte
Properties	Resistance and washability.
Thinner	Water
Drying time	Dry to touch 45 minutes. Over-coating time: 130 minutes.
Spread Rate	8-10 m <sup>2</sup> /litre.

We assume no liability if the result is affected by factors beyond our control. The user should check that the product supplied fits the needs for which it is intended and must perform a preliminary test if necessary. The information contained in this form should be used like a guide but not like a warranty. For more information in relation to safety and environment, see data safety sheet of the product

## PRODUCT DATA : BASE PAINT

### DESCRIPTION:

Matte paint available in different colours depending on the colours chart. Could be applied directly on the surface or be used to obtain different colour schemes

### APPLICATION

Product suitable for interior walls and ceilings.

### PROPERTIES:

- Finish: matte
- Excellent quality-price ratio
- Breathable
- Washable
- No splashing

### TECHNICAL CHARACTERISTICS:

Density: 1.37 kg/l.

Viscosity: 131 KU

Drying time: dry to touch 45 min. Over-coating : 130 min.

VOC EU limit value for the product (cat. A/a):  
75 g/l (2007) - 30 g/l (2010)

Max. VOC content: 20 g/l

Theoretical Spread rate\* 8-10 m<sup>2</sup>/l.

\* The coverage depends on the type and condition of the surface, on the absorption of the surface as well as the mode of application and the degree of dilution.

### INSTRUCTIONS:

Surfaces to be painted must be dry and free of impurities like dust, efflorescence, rust, grease, wax, etc. and primed properly. If the surfaces are already painted and they are in good condition, clean and apply a coat of paint. Homogenize well the product before application.

Paint Thinner: Water

To be used as a tincture, pour directly into the paint to be tinted. Add gradually until you get the desired colour.

To be used directly as a tinted or coloured paint, dilute with 5% water. It will be necessary to apply two coats.

It can be applied with a brush, roller or sprayer

Cleaning of tools: water

### CAUTIONS:

Do not apply under 5°C or over 40°C in the sun. Keep containers out of direct radiation. Keep out of reach of children.

### PACKAGING

1kg	0,73l
5kg	3.8l.