



PRODUCT DATA: SYNTHETIC ENAMEL

Fast drying enamel, hard and elastic. Excellent weather resistance, grease, washing, etc.. It is available in white which is very resistant to yellowing and mixable in different colours which can be mixed.

TECHNICAL CHARACTERISTICS

Nature:	Modified Alkyd .
Finish:	Gloss, satin or matte, see catalogue.
Colour:	White and chart colour
Density:	1,1 and 1,2 Kg/Litre, depending on colours.
Spread Rate	12-14 m ² /Litre each coat depending on the surface.
Drying time	Dry to touch 1-2 hours. Over-coating time: 6-12 hours
Packaging	4 Litres, 750 and 375 ml.

We assume no liability if the result is affected by factors beyond our control. The user should check that the product supplied fits the needs for which it is intended and must perform a preliminary test if necessary. The information contained in this form should be used like a guide but not like a warranty. For more information in relation to safety and environment, see data safety sheet of the product

PRODUCT DATA: SYNTHETIC ENAMEL

APPLICATION

Interior and exterior decoration and protection.
Suitable to paint doors, furniture, machinery, railings
and balconies, etc.

INSTRUCTIONS:

Application:	Brush , Roller or Paint Sprayer.
Dilution approx.:	5% 20%
Thinner and tools cleaning :	Solvent 103-X.

Once dissolved, apply thin layers on clean and primed surfaces.

Surface preparation:

Plaster and wood: Extra matt sealing paste.

Iron and steel: antioxidant primer, Red lead, etc.

Galvanized or aluminum: versatile and polyvalent primer.

Do not wash painted surfaces before 15 days.

On old, well-adhered surfaces, wash and sand gently and paint directly with
synthetic enamel.

On paints in poor condition, remove completely and prepare the surfaces as
mentioned above

CAUTIONS:

Flammable.

Stir the contents of the pack.

Use under adequate ventilation. Avoid prolonged
inhalation and use mask if necessary.