



PRODUCT DATA: PROTECTIVE PRIMER 467

1. DESCRIPTION

Impregnating primer for wood. It protects in depth preventing woodworm, fungi and water filtration. Excellent base to varnish exterior and interior surfaces, prolongs considerably the duration of the finishing varnish.

2. APPLICATIONS

Protection of windows and shutters, doors, beams, cantilever roofs, etc., and works of protection and maintenance of wooden structures in general

3. TECHNICAL CHARACTERISTICS:

Nature:	Special Alcydic .
Finish:	Matte.
Colour:	Colourless
Density:	0,85 Kg/L.
Spread rate:	8-12 m ² /Litre / coat depending on the surface.
Drying time:	Dry to touch : 2-4 hours, Over-coating 8-12 hours
Packaging	0,75, 4 and 20 Litres



PRODUCT DATA: PRODUCT DATA: PROTECTIVE PRIMER 467

4. INSTRUCTIONS:

Application: Brush or dip.

Diluent and tools cleaning: Solvent 103-I.

Woods to be treated must be clean, dry and free of varnish or paint that prevents penetration of Protective Primer

Apply abundantly, especially in the most absorbent areas.

New wood: Apply 1 or 2 consecutive coats of Protective Primer

Varnished wood: Remove completely the varnish or paint with paint remover and proceed as new wood.

Old unpainted wood: Remove completely the grayish and parched surface by sanding or slashing thoroughly until reaching the wood in good condition

5. CAUTIONS.

Flammable.

Use under adequate ventilation. Avoid prolonged inhalation and use mask if necessary.

Stir the contents of the pack.

