



PRODUCT DATA : LUNA PAINT

Low cost plastic paint (water-based) . Suitable for DIY (do-it-yourself project) due to its characteristics of whiteness and covering power.

Product	Plastic paint Luna Matte
Application	Walls and ceilings
Tools	Brush , Roller or Paint Sprayer.
Colour	White
Finish	Matte
Properties	Excellent resistance and whiteness for construction works and DIY.
Thinner	Water
Drying time	Dry to touch 30 minutes. Over-coating time: 60 minutes.
Spread Rate	5-7 m2/litre.

We assume no liability if the result is affected by factors beyond our control. The user should check that the product supplied fits the needs for which it is intended and must perform a preliminary test if necessary. The information contained in this form should be used like a guide but not like a warranty. For more information in relation to safety and environment, see data safety sheet of the product

PRODUCT DATA : LUNA PAINT

DESCRIPTION:

Low cost plastic paint (water based) .
Suitable for DIY (do-it-yourself project)
due to its characteristics of whiteness and
covering power.

APPLICATION

Product suitable for interior walls and
ceilings.

PROPERTIES:

- Finish: matte
- Excellent quality-price ratio
- Breathable
- Washable
- Colour: white
- No splashing

CAUTIONS:

Do not apply under 5°C
or over 40°C in the sun.

Keep containers out of
direct radiation. Keep
out of reach of children.

PACKAGING

5kg	3l
20kg	12.3l

TECHNICAL CHARACTERISTICS:

Vehicle: styrene acrylic copolymer

Pigments: calcium carbonate

Density: 1.643 kg/l.

Viscosity: 1.7 KU

Drying time: dry to touch 30 minutes.

Over-coating : 60 minutes.

VOC EU limit value for the product (cat. A/
a): 75 g/l (2007) - 30 g/l (2010)

Max. VOC content: 20 g/l

Theoretical Spread rate* 5-7 m²/l.

* The coverage depends on the type and
condition of the surface, on the absorption
of the surface
as well as the mode of application and the
degree of dilution.

INSTRUCTIONS:

Surfaces to be painted must be dry and free
of impurities like dust, efflorescence, rust,
grease, wax, etc. and primed properly. If the
surfaces are already painted and they are in
good condition, clean and apply a coat of
paint. Homogenize well the product before
application.

Paint Thinner: Water

Dilution:

-First coat: 15-20 % water

-Second coat: 5-10 % water

It can be applied with a brush, roller or
sprayer

Cleaning of tools: water