

PRODUCT DATA: EXTERIOR SIL PASTE

Aqueous paste based on mineral fillers, cold water dispersible and specially developed for the economical coating of interior or exterior surfaces.

APPLICATION Exterior use.

TECHNICAL CHARACTERISTICS:

Humidity: 30% Approx pH: 9 Approx Solid content: 73% Density: 1.85 kg / l Solubility: Dispersible in cold water. **Preservation:** Contains antiferments.

PACKAGING:

Bags: 2 kg or 5 kg.

CAUTIONS:

Do not apply under 5°C or over 40°C in the sun.Keep containers out of direct radiation. Keep out of reach of children.

We assume no liability if the result is affected by factors beyond our control. The user should check that the product supplied fits the needs for which it is intended and must perform a preliminary test if necessary.

The information contained in this form should be used like a guide but not like a warranty. For more information in relation to safety and environment, see data safety sheet of the product

PROPERTIES:

Easy to apply. Quick drying. Good adhesion. Easy to smooth Water repellent

INSTRUCTIONS:

Dilution: We recommend using this product in a concentration of 25% tempera paste with 75% water. The product must be perfectly homogenized before its application. Surfaces to be painted must be dry and free of impurities such as dust, efflorescence, rust, grease, wax, etc. and properly primed.