



PRODUCT DATA : SWIMMING POOL PAINT

White or blue plastic paint for pools. It has fungicide characteristics to prevent yeast and mold growth. It provides good coverage and toughness against chemicals typically used to maintain swimming pools.

Product	Paint for swimming pools
Application	Swimming pools
Tools	Brush , Roller.
Colour	Blue and White
Finish	Semi-gloss
Properties	Resistance to water and algae growth.
Thinner	Water
Drying time	Dry to touch 30 minutes. Over-coating time: 6 hours.
Spread Rate	8-10 m ² /litre.

We assume no liability if the result is affected by factors beyond our control. The user should check that the product supplied fits the needs for which it is intended and must perform a preliminary test if necessary. The information contained in this form should be used like a guide but not like a warranty. For more information in relation to safety and environment, see data safety sheet of the product

PRODUCT DATA : SWIMMING POOL PAINT

DESCRIPTION:

White or blue plastic paint for pools. It has fungicide characteristics to prevent yeast and mold growth. It provides good coverage and toughness against chemicals typically used to maintain swimming pools.

APPLICATION

Swimming pools.

PROPERTIES:

- Excellent quality-price ratio
- Good covering power
- Washable
- Resistance against chemicals typically used to maintain swimming pools.
- Colour: blue/white
- No splashing

CAUTIONS:

Do not apply under 5°C or over 40°C in the sun.

Keep containers out of direct radiation. Keep out of reach of children.

TECHNICAL CHARACTERISTICS:

Vehicle: styrene acrylic copolymer

Density: 1.46 kg/l.

Viscosity: 110 KU UNE-48-076-86

Drying time: dry to touch 45 minutes.

Over-coating : 6 hours.

VOC EU limit value for the product (cat. A/a): 75 g/l (2007) - 30 g/l (2010)

Max. VOC content: 20 g/l

Theoretical Spread rate* 8-10 m²/l.

* The coverage depends on the type and condition of the surface, on the absorption of the surface as well as the mode of application and the degree of dilution.



PACKAGING

5kg	3.5l.
20kg	14l

INSTRUCTIONS:

Surfaces to be painted must be dry and free of impurities like dust, efflorescence, rust, grease, wax, etc. and primed properly. If the surfaces are already painted and they are in good condition, clean and apply a coat of paint. Homogenize well the product before application.

Paint Thinner: Water

Dilution:

-First coat: 15-20 % water

-Second coat: 5-10 % water

It can be applied with a brush, roller or sprayer

Cleaning of tools: water