



PRODUCT DATA : SPORT FACILITIES PAINT

This paint provides a suitable finish for this type of facings since it has great adhesion to the substrate and a high resistance to abrasion and external conditions.

Product	Paint for sport facilities
Application	Padel, tennis courts etc..
Tools	Brush , Roller.
Colour	Blue, Green and Red
Finish	Matte
Properties	Resistance to water and algae growth.
Thinner	Water
Drying time	Dry to touch 30 min. Over-coating time: 6-8 hours. UNE 48-086-64
Spread Rate	6-8 m2/litre.

We assume no liability if the result is affected by factors beyond our control. The user should check that the product supplied fits the needs for which it is intended and must perform a preliminary test if necessary. The information contained in this form should be used like a guide but not like a warranty. For more information in relation to safety and environment, see data safety sheet of the product

PRODUCT DATA : SPORT FACILITIES

DESCRIPTION:

PAINT

This paint provides a suitable finish for this type of facings since it has great adhesion to the substrate and a high resistance to abrasion and external conditions. This paint is available in three colours: green, red and blue.

APPLICATION

Padel, tennis courts, etc...

PROPERTIES:

- Excellent quality-price ratio
- Good covering power
- Washable
- Resistance to abrasion.
- Colour: blue, green or red
- Resistant to external conditions

CAUTIONS:

Do not apply under 5°C or over 40°C in the sun.

Keep containers out of direct radiation. Keep out of reach of children.

TECHNICAL CHARACTERISTICS:

Vehicle: styrene acrylic copolymer

Density: 1.7 kg/l.

Drying time: dry to touch 30 minutes.

Over-coating : 6 hours.

VOC EU limit value for the product (cat. A/a): 75 g/l (2007) - 30 g/l (2010)

Max. VOC content: 20 g/l

Theoretical Spread rate* 6-8 m²/l.

* The coverage depends on the type and condition of the surface, on the absorption of the surface as well as the mode of application and the degree of dilution.



PACKAGING

5kg	3.5l.
20kg	14l

INSTRUCTIONS:

Surfaces to be painted must be dry and free of impurities like dust, efflorescence, rust, grease, wax, etc. and primed properly. If the surfaces are already painted and they are in good condition, clean and apply a coat of paint. Homogenize well the product before application.

Paint Thinner: Water

Dilution:

-First coat: 15-20 % water

-Second coat: 5-10 % water

It can be applied with a brush, roller or sprayer

Cleaning of tools: water