



PRODUCT DATA : PITTED AND DRIPPED PLASTIC PAINT

Painting paste water-based with high hardness, high viscosity. This paint allows embossed finishes and hides the flaws or imperfections of the wall if necessary.

Product	Pitted And Dripped Matte plastic paint
Application	Interior walls
Tools	Brush , Roller or Paint Sprayer.
Colour	White
Finish	Matte
Properties	Resistance , whiteness and covering power
Thinner	Water
Drying time	Dry to touch 4 hours. Over-coating time: 24 hours.
Spread Rate	6-8 m ² /litre.

We assume no liability if the result is affected by factors beyond our control. The user should check that the product supplied fits the needs for which it is intended and must perform a preliminary test if necessary. The information contained in this form should be used like a guide but not like a warranty. For more information in relation to safety and environment, see data safety sheet of the product

PRODUCT DATA : PITTED AND DRIPPED PLASTIC PAINT

DESCRIPTION:

Painting paste water-based with high hardness, high viscosity. This paint allows embossed finishes and hides the flaws/ imperfections of the wall if necessary.

APPLICATION

Product suitable for interior walls.

PROPERTIES:

- Finish: matte
- Easy to handle and apply
- Washable

CAUTIONS:

Do not apply under 5°C or over 40°C in the sun.

Keep containers out of direct radiation. Keep out of reach of children.

TECHNICAL CHARACTERISTICS:

Vehicle: styrene acrylic copolymer

Pigments: calcium carbonate

Density: 1.78 kg/l.

Viscosity: 150 KU

Drying time: dry to touch 4 hours. Over-coating : 24 hours.

VOC EU limit value for the product (cat. A/a): 75 g/l (2007) - 30 g/l (2010)

Max. VOC content: 20 g/l

Theoretical Spread rate* 6-8 m²/l.

* The coverage depends on the type and condition of the surface, on the absorption of the surface as well as the mode of application and the degree of dilution.

INSTRUCTIONS:

Surfaces to be painted must be dry and free of impurities like dust, efflorescence, rust, grease, wax, etc. and primed properly. If the surfaces are already painted and they are in good condition, clean and apply a coat of paint. Homogenize well the product before application.

Paint Thinner: Water

Dilution:

-First coat: 15-20 % water

-Second coat: 5-10 % water

It can be applied with a brush, roller or sprayer

Cleaning of tools: water



PACKAGING

22kg	12,5l
------	-------