



PRODUCT DATA:POLIMUL

Emulsion recommended to apply proper primers on walls and on matte interior paints.

PROPERTIES	UNIT	VALUE	METHOD
Solids Content	%	55±1	ISO 3251
Ph		6 - 7	ISO 976+
Viscosity broodfield RVT(1/50)	mPas	30 - 150	ISO 2555
TYPICAL EMULSION PROPERTIES			
Aspect		White emulsion	
MTFF	°C	1 Approx	ISO 2115
Particles size	mm	1 Approx	NQ 4039A
Protective colloid		Surfactant	
TYPICAL FILM PROPERTIES			
Aspect		Transparent,flexible	Subjective
Tg (DSC)	°C	10 Approx	NQ 4073A

We assume no liability if the result is affected by factors beyond our control. The user should check that the product supplied fits the needs for which it is intended and must perform a preliminary test if necessary. The information contained in this form should be used like a guide but not like a warranty. For more information in relation to safety and environment, see data safety sheet of the product



PRODUCT DATA: POLIMUL

DESCRIPTION:

Emulsion recommended to apply proper primers on walls and on matte interior paints.

APPLICATION

Product suitable for sealing masonry surfaces in interiors that will be finished with plastic paint.
Can be applied on any type of masonry surface.

PACKAGING:

1l and 4l

CAUTIONS:

Do not apply under 5°C or over 40°C in the sun.

Keep containers out of direct radiation. Keep out of reach of children.

INSTRUCTIONS:

Stir the contents of the container and add water according to use.

As a surface sealer: remove flakes and loose particles with a brush or other tools.

Dosage: one part of the product mixed with three parts of water.

To provide surface washability such as textured or tempera paints, apply directly.

Apply with a brush.

Cleaning of tools: water

